

2300°F / 1260°C: CerMax™ Extreme High Temperature, Heat & Flame Resistant Ceramic Twisted Fiber Rope: Premium & Industrial Grade



- A replacement and an alternative to asbestos. Highly flexible and minimal shrinkage.
- Melts above 3000°F / 1648°C.
- Produced from an extremely pure base fiber and can be used at 2300°F / 1260°C continuously with excursions to 3000°F / 1650°C.

Twisted Rope

CerMax™ Extreme High Temperature +Plus, Heat & Flame Resistant Ceramic Fiber Twisted Rope: Premium & Industrial Grade									
Part Number	Size			Spool length		Price per spool		Price per foot	
	inch	mm	-dash	feet	metres	Premium	Industrial	Premium	Industrial
R-C-T-X-M006-04-Y	.250	6	-04	900	274	\$ 700.16 / \$ 560.13		\$ 1.21 / \$ 0.93	
R-C-T-X-M010-06-Y	.375	10	-06	510	155	\$ 723.05 / \$ 578.44		\$ 2.21 / \$ 1.70	
R-C-T-X-M013-08-Y	.500	13	-08	750	228	\$ 1196.71 / \$ 957.37		\$ 2.48 / \$ 1.91	
R-C-T-X-M016-10-Y	.625	16	-10	500	152	\$ 1214.03 / \$ 971.22		\$ 3.78 / \$ 2.91	
R-C-T-X-M019-12-Y	.750	19	-12	375	114	\$ 1235.59 / \$ 988.47		\$ 5.14 / \$ 3.95	
R-C-T-X-M019-14-Y	.875	22	-14	275	83	\$ 1247.02 / \$ 997.61		\$ 7.07 / \$ 5.44	
R-C-T-X-M025-16-Y	1.000	25	-16	225	68	\$ 1267.98 / \$ 1014.38		\$ 8.79 / \$ 6.76	
R-C-T-X-M029-20-Y	1.250	32	-20	155	47	\$ 1279.66 / \$ 1023.73		\$ 12.88 / \$ 9.91	
R-C-T-X-M032-24-Y	1.500	38	-24	110	33	\$ 1293.15 / \$ 1034.52		\$ 18.34 / \$ 14.11	
R-C-T-X-M051-32-Y	2.000	51	-32	55	16	\$ 1306.48 / \$ 1045.18		\$ 37.08 / \$ 28.50	

For the "X" value in the part number: use "P" to specify Premium grade
use "I" to specify Industrial grade

For the "Y" value in the part number: use "SP" to specify full spool
use "FT" to specify By-The-Foot

Minimum Order for this product is \$50.00 for By-The-Foot Lengths